

HDC-HDBW3200

2Megapixel 1080P Vandal-proof IR HD-SDI Dome Camera



Model	DH-HDC-HDBW3200P	DH-HDC-HDBW3200N
Camera		
Image Sensor	1/3" 2Megapixel Exmor CMOS	
Effective Pixels	1920(H) x1080(V)	1920(H) x1080(V)
Electronic Shutter	Auto/Manual(1/3~1/10000s)	Auto/Manual(1/4~1/10000s)
Image Resolution	25fps@1080P(1920×1080)/720P(1280×720); 50fps@720P(1280×720)	30fps@1080P(1920×1080)/720P(1280×720); 60fps@720P(1280×720)
Min. Illumination	Color: 0.1Lux/F1.4, B/W: 0.01Lux /F1.4; 0Lux /F1.4(IR on)	
S/N Ratio	>52dB	
Video Output	1Vp-p Composite Output (75Ω/BNC)	
HD-SDI Video Output	1ch HD-SDI high -definition video (SMPTE 292M standard)	
Camera Features		
Max. IR LEDs Length	20m	
OSD	English, Chinese(Simplified/Traditional)	
Day/Night	Auto(ICR) / Color / B/W	
Backlight Compensation	BLC / DWDR	
White Balance	Auto/ Manual	
Gain Control	Auto / Manual	
Noise Reduction	2D	
Picture Adjustment	Mirror / Brightness / Contrast / Sharpness / Hue / Gain	

Lens	
Focal Length	3.3~12mm
Max Aperture	F1.4
Focus Control	Manual
Angle of View	H: 79.3°(Wide)~29.8°(Tele)
Lens Type	Manual / Auto iris (DC)
Mount Type	CS
Auxiliary Interface	
RS485	1 Port
General	
Power Supply	AC24V±10% / DC12V±10%
Power Consumption	<12W
Working Environment	-10 °C ~+60 °C, 10%~90%
Dimensions	Φ160mm×118.5mm
Weight	1.25Kg