

IPC-HDBW3110

1.3Megapixel HD Vandal-proof Network IR Dome Camera



Model	DH-IPC-HDBW3110P	DH-IPC-HDBW3110N
Camera		
Image Sensor	1/3" 1.3Megapixel PS CCD	
Effective Pixels	1280(H)x960(V)	
Scanning System	Progressive	
Electronic Shutter Speed	Auto/Manual 1/50~1/10000	Auto/Manual 1/60~1/10000
Min. Illumination	0.2lux/F1.4(color),0.01Lux/F1.4(B/W),0Lux(IR on)	
S/N Ratio	>50dB	
Video Output	1 channel BNC(1.0Vp-p, 75?)	
Camera Features		
Max. IR Length	20m	
Day/Night	Auto(ICR) / Color / B/W	
Backlight Compensation	BLC	
White Balance	Auto	
Gain Control	Auto/Manual	
Noise Reduction	2D	
Privacy Masking	Up to 4 areas	
Lens		
Focal Length	2.8~12mm	
Max Aperture	F1.4	

Focus Control	Manual	
Angle of View	H: 92°(Wide)~27.2°(Tele)	
Lens Type	Manual / Auto Iris (DC)	
Mount Type	CS	
Video		
Compression	H.264 / MJPEG	
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576) / CIF(352×288) /	1.3M(1280×960) / 720P(1280×720) / D1(704×480) / CIF(352×240) /
Frame Rate	Main Stream Sub Stream	1.3M(1~12fps)/720P(1 ~ 25fps) D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 10240Kbps	
Audio		
Compression	G.711a / G.711u (64kbps)/ PCM(128kbps)	
Interface	1/1 channel In/Out	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour	
ONVIF	ONVIF Ver. 2.0	
Max. User Access	10 users	
Smart Phone	iPhone, iPad, Android, Windows Phone	
Auxiliary Interface		
Memory Slot	Micro SD, Max 32GB	
Alarm	2/1 channel In/Out	
General		
Power Supply	DC12V/AC24V, PoE(802.3af)	
Power Consumption	<10W	
Working Environment	-10°C~+60°C, 10%~90%	
Protection Level	IK10 & IP66	
Dimensions	Φ160mm×118.5mm	
Weight	1.25kg	